



www.suntexcomposite.com

# TECHNICAL DATA SHEET

STYLE: TGF2050-VE236-5009

## DESCRIPTION

TGF2050-VE236-5009 is a heavy weight woven texturized fiberglass fabric coated with a specially formulated vermiculite dispersion which provides high temperature and abrasion resistance properties for the manufacturer of gaskets, flexible expansion joints, removable jackets and other types of fire control systems.

## BASE FABRIC

Base fabric style No. TGF2050

	<u>(Metric)</u>	<u>(English)</u>	<u>Test methods</u>
<b>Weave</b>	Plain	Plain	
<b>Yarn</b>			
Warp	ET9 1800 tex	ETG 2.78	
Weft	ET9 3600 tex	ETG 1.39	
<b>Construction</b>			
Warp	6 ± 0.6 ends/cm	15 ± 2 ends/inch	ASTM D 3775-96
Weft	2.5 ± 0.5 picks/cm	6 ± 1 picks/inch	ASTM D 3775-96
<b>Weight</b>	2050 ± 100 g/m <sup>2</sup>	60 ± 2.9 oz/yd <sup>2</sup>	ASTM D3776-96
<b>Thickness</b>	3.0 ± 0.3 mm	0.118 ± 0.011 inch	ASTM D1777-96

## COATED FABRIC

Coating style No. VE236-5009

<b>Coating</b>	Vermiculite coated on both sides		
<b>Weight</b>	2180 ± 50 g/m <sup>2</sup>	64 ± 1.5 oz/yd <sup>2</sup>	ASTM D3776-96
<b>Thickness</b>	3.0 ± 0.2 mm	0.118 ± 0.0078 inch	ASTM D1777-96
<b>Color</b>	Tan		
<b>Temp resistance</b>	750°C	1400°F	

All data in this specification sheet are representative which we believe to be accurate, but is given without guarantee or responsibility on our part. Anyone intending to use recommendation herein should make their own assessment of the suitability for the purpose required.

**SUNTEX COMPOSITE INDUSTRIAL CO., LTD.**  
1212 Fortune International Building, 717 Wuluo Road, Wuhan  
CHINA 430072  
Tel: +86-27-878 69 042  
Fax: +86-27-871 64 892  
Email: [suntex@public.wh.hb.cn](mailto:suntex@public.wh.hb.cn)  
[info@suntexcomposite.com](mailto:info@suntexcomposite.com)