



www.suntexcomposite.com

TECHNICAL DATA SHEET

STYLE: GF430P-SI244-1017

DESCRIPTION

GF430P-SI244-1017 is a medium weight woven fiberglass fabric with a specially formulated, flame retardant silicone rubber coating. GF430P-SI244-1017 is designed for removable insulation covers, dust lagging and other fire control systems.

BASE FABRIC

Base fabric style No. GF430P

	<u>(metric)</u>	<u>(English)</u>	<u>Test methods</u>
Weave	4H Satin	Crowfoot	
Yarn			
Warp	EC9 68 1 * 2	ECG 75 1/2	
Weft	EC9 68 1 * 2	ECG 75 1/2	
Construction			
Warp	18 ± 1 ends/cm	48 ± 3 ends/inch	ASTM D 3775-96
Weft	12.6 ± 1 picks/cm	32 ± 3 picks/inch	ASTM D 3775-96
Weight	430 ± 30 g/m ²	12.6 ± 0.9 oz/yd ²	ASTM D3776-96
Thickness	0.37 ± 0.06 mm	0.015 ± 0.002 inch	ASTM D1777-96

COATED FABRIC

Coating style No. SI244-1017

Coating	Silicone rubber 2 sides		
Weight	590 ± 25 g/m ²	17.4 ± 0.74 oz/yd ²	ASTM D3776-96
Thickness	0.45± 0.02 mm	0.018 ± 0.0007 inch	ASTM D1777-96
Color	Red		
Fire resistance	Flame retardant		
Temp resistance	Glass fabric up to 550 ⁰ C (1000 ⁰ F) Silicone rubber coating up to 250 ⁰ C (480 ⁰ F)		

All data in this specification sheet are representative which we believe to be accurate, but is given without guarantee or responsibility on our part. Anyone intending to use recommendation herein should make their own assessment of the suitability for the purpose required.

SUNTEX COMPOSITE INDUSTRIAL CO., LTD.
1212 Fortune International Building, 717 Wuluo Road, Wuhan
CHINA 430072
Tel: +86-27-878 69 042
Fax: +86-27-871 64 892
Email: suntex@public.wh.hb.cn
info@suntexcomposite.com