



www.suntexcomposite.com

TECHNICAL DATA SHEET

STYLE: GF430P-PU21B-2007

DESCRIPTION

GF430P-PU21B-2007 is a medium weight fiberglass fabric coated with a specially formulated polyurethane polymer.

GF430P-PU21B-2007 is the fabric applied for textile air distribution system. The other applications for the manufacturer of smoke and fire curtains, blinds, cavity wall fire barriers and other types of smoke and fire control systems.

BASE FABRIC

Base fabric style No. GF430P

	<u>(Metric)</u>	<u>(English)</u>	<u>Test methods</u>
Weave	4H Satin	Crowfoot	
Yarn			
Warp	EC9 136 1 * 0	ECG 37 1/0	
Weft	EC9 136 1 * 0	ECG 37 1/0	
Construction			
Warp	18 ± 1 ends/cm	48 ± 3 ends/inch	ASTM D 3775-96
Weft	12.6 ± 1 picks/cm	32 ± 3 picks/inch	ASTM D 3775-96
Weight	430 ± 30 g/m ²	12.6 ± 0.9 oz/yd ²	ASTM D3776-96
Thickness	0.37 ± 0.06 mm	0.015 ± 0.002 inch	ASTM D1777-96

COATED FABRIC

Coating style No. PU21B-2007

Coating	Fire retardant, high performance, grey/white polyurethane on both sides		
Weight	460 ± 20 g/m ²	13.5 ± 0.59 oz/yd ²	ASTM D3776-96
Thickness	0.41 ± 0.03 mm	0.017 ± 0.0012 inch	ASTM D1777-96
Color	Grey/white		
Fire resistance	M0 approvals		NF 92507
Temp resistance	Glass fabric up to 550 ^o C (1022 ^o F) Polyurethane coating up to 180 ^o C (356 ^o F)		

All data in this specification sheet are representative which we believe to be accurate, but is given without guarantee or responsibility on our part. Anyone intending to use recommendation herein should make their own assessment of the suitability for the purpose required.

SUNTEX COMPOSITE INDUSTRIAL CO., LTD.
1212 Fortune International Building, 717 Wuluo Road, Wuhan
CHINA 430072
Tel: +86-27-878 69 042
Fax: +86-27-871 64 892
Email: suntex@public.wh.hb.cn
info@suntexcomposite.com